T-CLEAN ACTION (S-5)

Pickling (Liquid Form)



- The Product acts quickly.
- This product is used as a Wipe process.
- Product is ASTM A-380 Certified.

Product Description

T-Clean Action (S-5) Weld Clean American utilises innovative standard technology for the high-adhesion formulation of a stainless steel pickling chemical. product is ASTM Certified. lt is used to clean Stainless steel component and also a large tanks. T-Clean Action (S-5) professionally leaves а clean finished stainless steel.

Product Application

- Boiler & Heat Exchanger
- Pressure Vessels.
- S.S. Storage Tank.
- S.S. Food & Pharma Equipment.
- Stainless Steel Weld Components

Product Benefits

- One-step treatment for easy application.
- This is typically used to clean complex objects, specifically the without welded stainless steel sheet.
- The product acts quickly.
- Product clean complicated items and also a large tank with the use of the wipe process.
- T-clean Action S-5 can remove weld oxide scale, and discolour shade for a uniform surface inside.

Storage & Disposal

- Store in a well-ventilated place.
 Keep the container tightly closed
- Temperature below 30 40 C.









Physical & Chemical Properties

Nitric Acid / HNO: - 20 %

HF:-7 %

5 % Soft Solution:-

Boiling Point:-120 C

Specific Gravity: - 1.24 - 1.26

Water Solubility: - Freely soluble in water

Vapour Density:- > Air

white liquid Appearance:-

Colour:-Opaque

1.4 - 1.8 g/cm3 at 30 C Density:-

Instruction

- · Avoid contact with eyes, skin, and body. Wear a gas mask, rubber gloves, acid-resistant clothes, and face shield goggles.
- · Wash with a water jet or mop with running water.
- Wear Safety glasses with splash shields or face shields.

Product Uses

- Before using T-Clean Action (S-5), Clean the article with water using a water jet pump.
- Fill the T-Clean Action S-5 chemical in a T-Clean Spray bottle and spray it on the surface uniformly.
- Take care for 10-15 min that the chemical will not dry on equipment.
- To clean and rinse the surface, wipe with a scrub pad and use clean running water either water jetting pump.





