

# T-CLEAN SOFT SOLUTION (S-4)

Metal Degreaser (Alkaline Base)



Since 2006

- Easily remove oily surface from Large Equipment.
- Used product on vertical and overhead surfaces.
- Product is ASTM A-380 Certified.

## Product Description

T-Clean Soft solution (S-4) utilises innovative Australian technology for the formulation of a high-adhesion stainless steel metal degreaser (Alkaline Base). **The product is ASTM A-380 Certified.** It is used to remove from all over the metal surface remove oil, grease, and other partials. T-Clean Soft Solution S-4 provides a professional finish to stainless steel surfaces, leaving them clean and oil-free.

## Product Application

- Boiler & Heat Exchanger
- Pressure Vessels.
- S.S. Storage Tank.
- S.S. Food & Pharma Equipment.
- Stainless Steel Weld Components

## Product Benefits

- After Degreasing (S-4) on component product will be neutralized and will drain out.
- Applying the Degreasing component will be oil-free so that the pickling process can be done easily.
- After use degreasing there will be no patch seen of pickling on the component
- After applying (S-4) degreasing you will save time in pickling, and the wastage of pickling chemicals will decrease.

## Storage & Disposal

- Store in a well-ventilated place. Keep the container tightly closed
- Temperature below 30 - 40 C.





## Physical & Chemical Properties

Soda ASS :-	10%
Caustic Lie :-	40%
Ph :-	6 Ph
Boiling point :-	90 F
VOC content :-	42 LBS/GAL
Solubility in water :-	Complete
Appearance :-	Opaque
Evaporation rate :-	1.2 (water=1.0)
Ratio Content :-	1/Powder 4/Water

## Instruction

- Avoid contact with eyes, skin, and body. Wear a gas mask, rubber gloves, acid-resistant clothes, and face shield goggles.
- Do not carry on the process in direct sunlight or when your equipment is hot.
- Do let the chemical get dry on your job for 10-15 minutes.
- Apply the chemical uniformly on your equipment.

## Product Uses

- First of all mix T-Clean soft solution (S-4) in ratio of 1 : 4, 1 powder, and 4 water.
- Before using T-clean (S-4) clean the surface with a Water Jet or mopping with running water.
- Apply T-clean soft solution S-4 pickling chemical with a T-clean spray Pump.
- Apply the chemical on equipment in a uniformly manner.
- Take care for 10-15 min that the chemical will not dry on equipment.
- After that clean the surface with Water Jetting or mopping with clean running water.
- After cleaning the equipment let them dry in a natural atmosphere.

