

### TECHNO SERVICES

#### PICKLING &PASSIVATION CHEMICALS MFG

#### **MATARIAL SAFETY DATA SHEET**

#### 1.PRODUCT AND COMPANY IDENTIFICATION

Product Name :- T-Clean Metal Cleaner

Package :- 5 Kg container

Application :- Before Pickling & Passivation of Stainless steel

Product Use :- Metal Cleaner

Item brand :- T-Clean

Manufacturer :- Techno services

Physical Address :- 242/243, G.I.D.C kabilpor,396424, P.O. Box no.396424

Business Phone :- 99245-59751 /7622005114

E-mail Address :- tcleannvs@gmail.com

Web Address :- www.tclean.in

#### 2.INGREDIENTS

MATERIAL	CAS#	% BY WT.
Soda Ass	497-19-8	10%
Costic Lie	1310-73-2	60%
Water /Powder		30%

#### 3.HAZARD IDENTIFICATION

#### **Emergency Overview:-**

Oil Cleaner Degreaser is Non-Corrosive, Non-Toxic, and does not pose any known acute or chronic physical hazards.

PLOT: 242 / 243, G.I.D.C., KABILPORE, NAVSARI - 396 424. TEL.: 7622005114/ Mobile: +91 99245 59751 E-Mail: tcleannvs@gmail.com/ rdeepeshg@yahoo.com / web.www.tclean.in



# TECHNO SERVICES PICKLING & PASSIVATION CHEMICALS MFG

Carcinogenic: NTP or OSHA does not consider this product a carcinogen

#### Effects of Overexposure:

**Skin** :- Non-Corrosive. No effect under normal use. Product may cause irritation or rash to

those with hypersensitivity. Prolonged contact may result in dryness and ulceration.

**Eyes** :- Can cause eye irritation.

Ingestion: Non-Toxic per Consumer Product Safety Commission and FHSA standards. Acute oral

LD50 greater than 5 g/kg.

**Inhalation**: No effect under normal use. Excessive inhalation may cause irritation of the

respiratory passages.

#### 4. FIRST AID MEASURES

**Skin Contact**:- Remove contaminated clothing. Rinse skin with warm water for 15 minutes. If irritation occurs seek medical attention.

**Eye Contact**:- Flush with water for 15 minutes. If irritation persists seek medical attention.

**Ingestion** :- Drink large quantities of water. Call physician immediately.

**Inhalation** :- Remove to fresh air immediately. If irritation persists, contact physician.

#### 5. FIRE AND EXPLOSION HAZARD

Flammability of the product	Non Flammable	
Flash Point	None to Boiling	
Extinguishing Media	Dry Chemical, Water Fog, Co2, Sand	
Fire Fighting Procedures	Wear Self Contained Breathing Apparatus	
Products of combustion	Carbon oxides	
Fire Hazards in the presence of other chemicals	No specific information is available	
Unusual Fire Hazards	None Expected	

PLOT: 242 / 243, G.I.D.C., KABILPORE, NAVSARI - 396 424. TEL.: 7622005114/ Mobile: +91 99245 59751 E-Mail: tcleannvs@gmail.com/ rdeepeshg@yahoo.com / web.www.tclean.in



## FICKLING & PASSIVATION CHEMICALS MFG

#### 6. ACCIDENTAL RELEASE MEASURES

Small Spill :- Absorb with industrial absorbent. Dispose of in accordance with local,

state & federal regulations. Rinse residue to avoid slippery conditions.

Large Spill :- Non-flammable material. Wear chemical resistant gloves, boots and

goggles. Stop the source of the spill. Collect the spill using mechanical

means.

Waste disposal method: Fully water-soluble. Follow all local, state and federal regulations.

#### 7. HANDLING & STORAGE

**Precautions** :- Store containers upright in cool dry place.

**Storage** :- Store product in original containers. Do not store in metal vessels.

**Other precautions** :- Keep out of reach of children.

#### 8. EXPOSURE CONTRIOLS & PERSONAL PROTECTION

#### **Engineering Controls:**

No control measures are required under normal conditions. If large quantities are involved use NIOSH or MSHA approved respirator Limited personal exposures exist with this product. As always keep airbone vapors below TLV limits. Ensure that proper work-station safety mechanisms are operative and tested including showers and eyewash stations.

#### Personal Protection:-

Safety glasses are recommended, chemical resistant gloves aprons and suits are optional for those with dermatological sensitivity.

#### 9. ECOLOGICAL DATA

Non-toxic to Aquatic Organisms Fathead Minnow (Pimephales promelas) LC50 > 200mg/L at 96 hours.



### **TECHNO SERVICES**

#### PICKLING &PASSIVATION CHEMICALS MFG

#### 10. PHYSICAL DATA

Boiling point :- 2000 F

Voc content :- 42 LBS/GAL

Vapor pressure :- 4.0 mm Hg @ 77 F (ASTM D-2879)

Solubility in water :- COMPLETE

Appearance and odor :- Clear Solution With A Characteristic Odor

Specific gravity :- 1.052 (ASTM 112H @ 20o C)

Evaporation rate :- 1.2 (water=1.0)

#### 11. REACTIVITY DATA

Conditions To Avoid :- Extreme Heat

Stability :- Stable

Polymerization :- Will Not Occur

Corrosivity :- Non-corrosive

#### 12. TOXICOLOGICAL DATA

Routes of Entry :- Eyes, skin, ingestion.

Toxicity to animals :- Non-Toxic per Consumer Product Safety Commission and FHSA

standards. Acute oral LD50 greater than 5 g/kg.

Effect on Humans :- None known.

Special Remarks :- None.

#### 13. DISPOSAL CONSIDERATIONS

Waste Disposal :- Dispose of in accordance with local, state & federal regulations. Rinse

residue to avoid slippery conditions.

PLOT: 242 / 243, G.I.D.C., KABILPORE, NAVSARI - 396 424. TEL.: 7622005114/ Mobile: +91 99245 59751 E-Mail: tcleannvs@gmail.com/ rdeepeshg@yahoo.com / web.www.tclean.in CLEAN

TECHNO SERVICES
PICKLING &PASSIVATION CHEMICALS MFG

14. TRANSPORT INFORMATION

DOT CLASSIFICATION: Not Applicable - Non-regulated; Non-hazardous.

15. REGULATORY INFORMATION

All components used in this compound appear on the TSCA Inventory.

Federal/National :- 2 Butoxyethanol

This chemical is subject to S.A.R.A. Title III section 313 part 372 reporting. The hazard communication standard requires that mixtures such as this product be assumed to present the same health hazards, as do the components that constitute at least 1% of the mixture. OSHA has, however, noted that the health hazards of the individual components may be reduced or altered by including them in a mixture.

16. OTHER INFORMATION

Person using this product. Product use and conditions of use are beyond the control of T-clean. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, This SDS format is in accordance with T-clean provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained expressed or implied, are made.

PLOT: 242 / 243, G.I.D.C., KABILPORE, NAVSARI - 396 424. TEL.: 7622005114/ Mobile: +91 99245 59751

E-Mail: tcleannvs@gmail.com/ rdeepeshg@yahoo.com / web.www.tclean.in